

TECHNICAL SPECIFICATION FOR TRV 45 BESPOKE	
VOLTS	120 V
AMPS	12.5 A
WATTS	1500 W
BTU	5120
HEATER - High	1500 W
HEATER - Low	750 W
NO HEATER	45.2 WATTS MAX
LAMPS - Quantity	150 PCS LED
LAMPS - Watts	0.5 W & 0.15 W & 0.06 W
TOTAL WATTS	31.4 W
STEP MOTOR	3AT 8.7 WATTS
APPLIANCE SIZE W*H*D	46 1/8" x 29 3/8" x 15"
	117.2 x 74.6 x 38.2 cm
GLASS VIEWING OPENING W1*H1	45" x 20"
	114.3 x 50.9 cm
SURROUND SIZE W2*H2*D2	45 1/4" x 29 5/8" x 13 1/4"
	114.8 x 75.2 x 33.6 cm
SHIPPING SIZE	51 5/8" x 18 7/8" x 34 5/8"
	131 x 48 x 88 cm
SHIPPING WEIGHT - Unit	155.5 LBS (70.7) KGS
PLUG LOCATION	LEFT SIDE
CORD LENGTH	70.9<L<95.5
APPROX HEATING AREA	400 SQ FT

TECHNICAL SPECIFICATION FOR TRV 55 BESPOKE

VOLTS	120 V	240V
AMPS	12.5 A	12.1A
WATTS	1500 W	3000 W
BTU	5120	10240
HEATER - High	1500 W	3000 W
HEATER - Low	750 W	1500 W
NO HEATER	46.3 WATTS MAX	46.3 WATTS MAX
LAMPS - Quantity	192 PCS LED	192 PCS LED
LAMPS - Watts	0.5 W & 0.15 W & 0.06 W	0.5 W & 0.15 W & 0.06 W
TOTAL WATTS	32.3W	32.3W
STEP MOTOR	3 AT 8.7 WATTS	3 AT 8.7 WATTS
APPLIANCE SIZE W*H*D	56 1/8" x 29 3/8" x 15"	
	142.7 x 74.6 x 38.2 cm	
GLASS VIEWING OPENING W1*H1	55" x 20"	
	139.7 x 50.9 cm	
SURROUND SIZE W2*H2	55 1/4" x 29 5/8" x 13 1/4"	
	140.2 x 75.2 x 33.6 cm	
SHIPPING SIZE	61 5/8" x 18 7/8" x 34 5/8"	
	156.4 x 48 x 88 cm	
SHIPPING WEIGHT	184.8 LBS (84) KGS	
PLUG LOCATION	LEFT SIDE	
CORD LENGTH	70.9<L<95.5	
APPROX HEATING AREA	400 SQ FT	

TECHNICAL SPECIFICATION FOR TRV 65 BESPOKE

VOLTS	120 V	240 V
AMPS	12.5 A	12.1 A
WATTS	1500 W	3000 W
BTU	5120	10240
HEATER - High	1500 W	3000 W
HEATER - Low	750 W	1500 W
NO HEATER	57.1 WATTS MAX	57.1 WATTS MAX
LAMPS - Quantity	218 PCS LED	218 PCS LED
LAMPS - Watts	0.5 W & 0.15 W & 0.06 W	0.5 W & 0.15 W & 0.06 W
TOTAL WATTS	43.3 W	43.3 W
STEP MOTOR	3 AT 8.7 WATTS	3 AT 8.7 WATTS
APPLIANCE SIZE W*H*D	66 1/8" x 29 3/8" x 15"	
	168.1 x 74.6 x 38.2 cm	
GLASS VIEWING OPENING W1*H1	65" x 20"	
	165.1 x 50.9 cm	
SURROUND SIZE W2*H2	65 1/4" x 29 5/8" x 13 1/4"	
	165.6 x 75.2 x 33.6 cm	
SHIPPING SIZE	71 5/8" x 18 7/8" x 34 5/8"	
	181.8 x 48 x 88 cm	
SHIPPING WEIGHT	211.2 LBS (96) KGS	
PLUG LOCATION	LEFT SIDE	
CORD LENGTH	70.9<L<95.5	
APPROX HEATING AREA	400 SQ FT	

TECHNICAL SPECIFICATION FOR TRV 75 BESPOKE

VOLTS	120V	240 V
AMPS	12.5 A	12.1 A
WATTS	1500 W	3000 W
BTU	5120	10240
HEATER - High	1500 W	3000W
HEATER - Low	750 W	1500 W
NO HEATER	67.7 WATTS MAX	67.7 WATTS MAX
LAMPS - Quantity	291 PCS LED	291 PCS LED
LAMPS - Watts	0.5 W & 0.15 W & 0.06 W	0.5 W & 0.15 W & 0.06 W
TOTAL WATTS	54.2 W	54.2 W
STEP MOTOR	3 AT 8.7 WATTS	3 AT 8.7 WATTS
APPLIANCE SIZE W*H*D	76 1/8" x 29 3/8" x 15"	
	193.5 x 74.6 x 38.2 cm	
GLASS VIEWING OPENING W1*H1	75" x 20"	
	190.5 x 50.9 cm	
SURROUND SIZE W2*H2	75 1/4" x 29 5/8" x 13 1/4"	
	191 x 75.2 x 33.6 cm	
SHIPPING SIZE	81 5/8" x 18 7/8" x 34 5/8"	
	207.2 x 48 x 88 cm	
SHIPPING WEIGHT	245.3 LBS (111.5) KGS	
PLUG LOCATION	LEFT SIDE	
CORD LENGTH	70.9<L<95.5	
APPROX HEATING AREA	400 SQ FT	

TECHNICAL SPECIFICATION FOR TRV 85 BESPOKE

VOLTS	120 V	240 V
AMPS	12.5 A	12.1 A
WATTS	1500 W	3000 W
BTU	5120	10240
HEATER - High	1500 W	3000 W
HEATER - Low	750 W	1500 W
NO HEATER	73.1 WATTS MAX	73.1 WATTS MAX
LAMPS -Quantity	335 PCS LED	335 PCS LED
LAMPS - Watts	0.5 W & 0.15 W & 0.06 W	0.5 W & 0.15 W & 0.06 W
TOTAL WATTS	59.6 W	59.6 W
STEP MOTOR	3 AT 8.7 WATTS	3 AT 8.7 WATTS
APPLIANCE SIZE W*H*D	86 1/8" x 29 3/8" x 15"	
	218.9 x 74.6 x 38.2 cm	
GLASS VIEWING OPENING W1*H1	85" x 20"	
	215.9 x 50.9 cm	
SURROUND SIZE W2*H2	85 1/4" x 29 5/8" x 13 1/4"	
	216.5 x 75.2 x 33.6 cm	
SHIPPING SIZE	91 5/8" x 18 7/8" x 34 5/8"	
	232.6 x 48 x 88 cm	
SHIPPING WEIGHT	280.5 LBS (127.5) KGS	
PLUG LOCATION	LEFT SIDE	
CORD LENGTH	70.9<L<95.5	
APPROX HEATING AREA	400 SQ FT	